

DDR5内存支持列表

注意：内存超频时建议使用2/4通道的插槽

厂商	部件号	规格	RAM 速度	运行速度	SS/DS	芯片品牌	时序	电压	插槽支持	插槽1/3频率支持
ADATA	AX5U5200C3816G-B	2X16GB	5200	5200	SS	Micron	38-38-38-70	1.25	2,4	4000
ADATA	AD5U48008G-B	8GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
Crucial	CT16G48C40U5.8A1	2X16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
Crucial	CT8G48C40U5.M4A1	2X8GB	4800	4800	SS	Micron	40-39-39-77	1.1	2,4	4000
GelL	semper	2x 16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
teclast	TLD58G48S10	16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
powev	semper	2X16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
ADATA	AD5U480016G-B	2X16GB	4800	4800	SS	Spectek	40-40-40-77	1.1	2,4	4000
team	TED516G4800C40BK	2X16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
SAMSUNG	M323R2GA3BB0-CQK0D	2X16GB	4800	4800	SS	SAMSUNG	40-39-39-77	1.1	2,4	4000
KINGSTON	KF552C40BBK2-32	2X16GB	5200	5200	SS	SKhynix	40-40-40-80	1.25	2,4	4000
SKhynix	HMCG78MEBUA	2X16GB	4800	4800	SS	SKhynix	40-40-40-77	1.1	2,4	4000
ADATA	AD5U480016G-B	2x16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
KINGSTON	KVR48U40BS8-16	2X16GB	4800	4800	SS	SKhynix	40-39-39-76	1.1	2,4	4000
GSKILL	F5-6000U4040E16G	2X16GB	6000	6000	SS	Samsung	40-40-40-76	1.3	2,4	4000
ADATA	X5U6000C4016G-B	2X16GB	6000	6000	SS	Samsung	40-40-40-76	1.35	2,4	4000
Lexar	LD5DU016G-H4800CNM2G8ST	2X16GB	4800	4800	SS	Micron	40-40-40-76	1.1	2,4	4000
Crucial	CT16G48C40U5GT.8A1	2X16GB	4800	4800	SS	Micron	40-40-40-77	1.1	2,4	4000
Crucial	CT16G48C40U5.M8A1	2X16GB	4800	4800	SS	Micron	40-39-39-76	1.1	2,4	4000